

Colour Sample

Properties

Flügger Colour Sample is an illustrative colour sample helping you to decide, which colour to buy. To be tinted in a tinting machine according to the Flügger colour card collection.



Application

For interior and exterior application for deciding on colour.

In order to obtain a reliable and satisfying result, it is important to follow the below-mentioned instructions.

The substrate must be clean, dry and solid.

Clean the substrate with Flügger Fluren 37 Basic Cleaner. Prime chalking and porous substrates with Flügger Sealer.

Apply the colour sample on an area of a certain size.

Apply some to a board in order to be able to carry it around to see it with different light incidences.

Apply by brush or by roller.

Please notice that different shades may occur, depending on the chosen material, light incidence and gloss level.

Please also refer to the information on the label as well as to the application guide on

Link="www.flugger.com"

Storage: Cool, frost-free and tightly closed

Technical Data

Product Type	Acrylic paint
Gloss	5;Matte
Density (kgs/l)	1,3
Nominal spreading rate (m ² /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	6
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Water Cleaning of tools etc: Water

Current TDS Version

January 2017