

## DETALE Topcoat

DETALE CPH is a line of exclusive decorative products to take care of the small details. Paints and finishes are inspired by our Nordic design heritage and the changeability of nature. The products are suitable for professional as well as do-it-yourself use.

### Product properties

Features-enhancing impregnation for walls and ceilings. Produces a water and dirt repelling surface. Recommended for premises with normal functional requirements, that are exposed to some dirt and wear and tear.

- **Impregnating**
- **Transparent**
- **Dirt resistance corresponding to a matt painted surface**



### Product use

Living rooms, entrances, offices, business premises, clinics, shops, hotels and restaurants.  
Surface treated with DETALE KC 14 and DETALE KABRIC as well as a mineral substrate of plaster, concrete and brick.

### Substrate

Must be absorbent, clean, dry, firm and suitable for surface treatment.

### Treatment

Remove dust and loose material.  
Apply 1-2 times. Maximum effect is achieved after 2 applications.

### Application

Microfibre cloth, dabbed on the surface.  
Apply if needed using a low pressure sprayer and subsequent dipping.  
Apply evenly wet-on-wet, avoiding runners.  
Avoid condensation formation.  
Cold and increased humidity extends drying time, full curing and recoating interval.  
Increased temperature and low atmospheric humidity reduce drying time and full curing.  
Always test for control and acceptance of adhesion and result.

### Expected result

Transparent surface.  
Withstands cleaning with a mild cleaning agent without abrasive material, water and drying with a moist cloth.  
Avoid placing loads on the surface before the treatment is fully cured.

## Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

## Storage

Cool, frost free and tightly closed

## Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

## Technical Data

Density (kgs/l)	1.0
Long spreading rate (m <sup>2</sup> /l.)	15
Short Spreading rate (m <sup>2</sup> /ltr.)	12
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Fully cured at 20° C, 60 % RH (Days)	28
Cleaning of Tools etc.	Water
Country of Origin	Denmark

## Current TDS Version

November 2024