

Facade Anti-green

Product properties

Concentrated cleaning agent for removal of fouling on all external surfaces.

- Efficient removal of fouling
- For cleaning and freshening
- Long-term effect



Labelling



Product use

For exterior use on facades, masonry, woodwork, roof tiles, glass, plastic, etc.

Substrate

Surfaces must be clean, dry, solid and suitable for treatment.

Treatment

To be used at +5 °C. Please notice that if the product is used at e.g. +20 °C the efficiency will increase and the waiting time will shorten correspondingly.

Application

Painted facade, repainting:

Apply the product, leave for 48 hours and wash the surfaces with facade cleaner. Let dry.

Painted facade, not repainting:

Apply the product, let it work for 48 hours and let the weather take care of the rest. If necessary, wash the surfaces with facade cleaner. Can be slightly corrosive to aluminium, zinc, copper and other porous metals. Protect sensitive green areas or wet with water before treatment.

Good practice

Frequently check for overgrowth on the surfaces, and remove such currently.

Expected result

Clean surface ready for paint treatment, if desired.

Cleaning and maintenance

Flügger Façade Anti-green is very suitable as preventive protection against fouling. Apply and let dry without washing off.

Please note!

Do not apply near or above surface water, such as lakes or streams.

Environmental information

Remove the cap before sorting the packaging for recycling.

Storage

Cool, frost-free and tightly closed

Supplementary Info

Shelf life: 60 months in unopened container.

Technical Data

Product Type	Cleaning
Mixing ratio	1:4 with water
Dosing	1:4
Nominal spreading rate (m ² /ltr.)	6
Min. working temp. during application and drying/curing	Min. +5°C
Dilution	Water
Cleaning of Tools etc.	Water

Current TDS Version

December 2024

Replaces TDS Version

February 2024