

Table Top Oil

Product properties

Matt oil for tabletops, furniture and similar. Saturates the surface of the wood and makes it water and dirt repellent. Natural Wood Table Top Oil cannot be tinted. Available in white, transparent and mahogany.

- Enhances the natural glow of the wood
- Good protection against dirt and water impact
- Documented suitable for food contact



Labelling



Product use

For indoor use on tabletops and furniture.

E.g. pine, spruce, oak, beech, ash, mahogany and teak.

Not suitable for floors.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Uneven or loose varnish and paint are completely removed to clean wood by sanding.

Remove dirt, grime, grease and chalking materials with Natural Wood Cleaner.

Sand the surface lightly with fine sandpaper, avoid sanding through.

Wipe dry with a hard-wrung cloth.

Optimum durability and results are achieved with 3 treatments before use.

On hardwoods, the best water resistance is achieved with an additional treatment.

Always carry out a test treatment to verify and accept the adhesion and result.

Application

Brush.

Apply the oil with a brush in an even and covering layer.

Wait for 30 min. while the oil penetrates the wood.

Apply more oil if dry areas appear.

Wipe off any excess oil with a lint-free cotton cloth.

The surface should be completely free of excess oil.

Let the tabletop rest for one hour and then repeat the treatment.

Condensation during drying/curing must not occur.

Expected result

Saturated surface with uniform gloss and finish.

The durability of the surface depends on wood quality, construction, application and exposure.

Cleaning and maintenance

Clean the surface as needed with universal cleaner or equivalent.

The surface can be refreshed with a thin layer of Natural Wood Table Top Oil applied with a fine application sponge.

Avoid heavy exposure to water and liquids for the first 4-7 days.

Please note!

Oil-saturated rags can self-ignite.

Saturate with water or destroy.

Environmental information

Minimise paint waste by calculating in advance how much paint to use.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as metal.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Wood stain
Gloss	10;Matte
Density (kgs/l)	0.84
Solids Weight %	35
Solids Vol. %	38
Nominal spreading rate (m ² /ltr.)	20
Long spreading rate (m ² /l.)	50
Short Spreading rate (m ² /ltr.)	10
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	7
Dilution	Do not dilute
Cleaning of Tools etc.	White spirit and brush cleaner
Country of Origin	Denmark

Current TDS Version

December 2024

Replaces TDS Version

April 2024